



TAB INSULATION

Reduces your carbon footprint.



T
A
B

I
N
S
U
L
A
T
I
O
N

Low-E Tab Material makes installing ESP Low-E® Insulation in residential stud cavities as easy as can be. Low-E Tab is cut to 16" or 24" on center so it can bene?t commercial buildings, structures with radiant heating as well as residential applications. The product is very easy to install and does not require special clothing or respirators to do so. The product is hypoallergenic and does not promote growth of mold or mildew.



Easy To Use!
Low-E Tab Insulation
*Interior Walls, Attic
Ceilings, Basement
Remodels & Many More
Uses!*

* The information contained herein pertains to only the product codes listed on the reverse side of this ?yer.

ESP LOW-E® TAB INSULATION

PRODUCT CODES: 16EFEC, 24EFEC, 18EFEC

PRODUCT DIMENSIONS & DESCRIPTION

Double sided scrimless aluminum foil laminated to polyethylene foam (1/4" nominal thickness)

WIDTH: 16", 24", 18" respectively

LENGTH: 125' (16" & 24"widths) 100' (18"width)

R-Value* : R-11 down R-7.55 up R-7.75 horizontal

PERM RATING: ASTM E-96 0.008

FLAME AND SMOKE: ASTM E-84

Flame spread <25 Smoke developed <50

EMITTANCE: ASTM C-1371 0.03

* R-value results are obtained from ASTM C236. R-values for tab materials can be higher or lower depending upon application.

Specific R-values for specific applications can be obtained from Install Guide at www.low-e.com or by contacting ESP, Inc. at 1-800-289-5693

Do not leave product exposed when placed on both walls and ceiling of a conditioned space if ceiling height is less than 10 feet. In conditioned spaces where product is being used on both walls and ceiling, and ceiling height is less than 10 feet, surfaces should be covered with a proper thermal barrier.

WARNING: Although ESP LOW-E® Insulation Products are all fire tested to ASTM and/or NFPA standards; it is recommended that they or any insulation material should not be exposed to open flame or other ignition sources of sufficient intensity during shipment, storage or installation.

CAUTION: Aluminum is an Electrical Conductor. Please use caution when working around electrical sources including overhead power lines. Carefully inspect electrical junction boxes and check for frayed wires before beginning installation.

Discover even more ways to lower energy costs with ESP LOW-E® Insulation



Green building is not just a trend, but the wave of the future as more and more homeowners and builders demand energy efficient homes and products. ESP Low-E® Insulation products are designed for maximum energy and cost efficiency. Whether it's under slab, under roof, around duct work or wrapping the entire house, ESP LOW-E® Reflective Insulation products save more money on heating and cooling than regular insulation and Housewrap. Check out all the ways ESP LOW-E® Insulation can help reduce your energy consumption around the home.



Scan code to see Install Guide



ESP LOW-E® Insulation • ESP LOW-E® Housewrap • ESP LOW-E® SlabShield

For more information and a free sample of LOW-E material, or for the dealer nearest you visit www.low-e.com or call 1.800.289.5693

ESP LOW-E is a trademark of Environmentally Safe Products, Inc. copyright©espnov1.2011